



## easyflex Basic P5N/easyflex plus Basic P5N Especially good value Clearspan tent

Available from 10 - 18 m, the easyflex offers an alternative among the Losberger De Boer large tent systems, combining high quality and an attractive price.

The material and construction offer the high standard of performance for which Losberger De Boer is renowned. Consistent optimization of basic features, simplification of the frame system and the omission of modular related features in particular, make this large tent system especially costeffective.

Are you looking for a quality system at an attractive price, but offering more options than the standard easyflex version? If so, the easyflex plus version is the right choice. It offers additional options for using the Losberger De Boer system cassette flooring and system wall elements of hard-PVC or glass.

easyflex or easyflex plus - the right choice when attractive price and perfect function matter.



## Dimensions

Туре	Profile	Frame ID#	Truss Profile	Width	Leg	Truss-	Rafter Selections	
						distance	Standard	Optional
easyflex	P5N	2	6" x 4 3/4" 150 mm x 120 mm	10 m	280/340 cm	- 5 m/16' -	5.0 m	-
				12 m	280/340 cm		6.0 m	5.6 m + 0.4 m
				15 m	280/340 cm		7.5 m	5.6 m + 2 m
				18 m	280/340 cm		9.0 m	5.6m + 3.5 m
easyflex (plus)	P5N	2	6" x 4 3/4" 150 mm x 120 mm	10 m	340 cm	5 m/16'	5.0 m	-
				12 m	340 cm		6.0 m	-
				15 m	340 cm		7.5 m	-

# Technology

Modular character for diverse combination and expansion. Trouble-free transport, storage and maintenance. Assembly with and without Losberger De Boer system cassette flooring possible. A host of accessories and special equipment. All system components are standard stock parts for fast availability. The interchangeable tent components within the system enable various configurations, different widths and extensions without expensive special solutions.

#### Covers

Textile covers made of polyester fabric, coated with PVC on both sides. Curtains with PVC-gliders for easy fitting in curtain groove. Side and gable curtains with standard plug fastening, lace and grommet or zippers. Side curtains with windows available in several attractive designs. System wall elements are available in glass or hard-PVC.









### Frame

Trusses of extruded 4-groove aluminum hollow profiles, maintenance-free, all aluminum components technically anodized. Steel parts are hot-dip galvanized. Truss distance 5m. Roof slope 18 degrees. Integrated curtain groove in eave purlins and gable wall beams. Prepared for a subsequent installation of system cassette wall elements of hard-PVC or glass. Structural lengths in 5 m increments. Exact joining of various Losberger De Boer large and small tent systems possible.

**Accessories & special equipment** 

- Roof covers and side curtains of transparent foil
- Aluminum doors (double-wing/one-wing)
- Glass & Cassette wallCassette floors
- Ramps at entrances
- Textile beam gutter or beam flap and many more...

For more details please visit our website www.losbergerdeboer.com

Losberger De Boer 285 Bucheimer Rd Suite A Frederick, MD 21701 Phone: 1-301-682-8000 Fax: 1-301-682-8005 E-Mail: LosbergerUS@losbergerdeboer.com www.losbergerus.com L512/werbemacher