



uniflex Basic P3N/uniflex Basic P2N Versatile, creative and economical

Special requirements call for unique solutions:

The Losberger De Boer uniflex Basic units, available from 10 - 30 m, are the ideal entry level product for large tent sytems. The continous modularity of this system makes it possible for you to turn one into two, and two into more, as only a few additional components are needed in order to produce a uniflex modular tent system in a wide variety of widths and designs. Everything in this system can be combined and interchanged while the fully developed technology of this particular modular system limits the number of necessary frame sections to an absolute minimum, thus guaranteeing efficient storage along with fast and easy assembly. Our cutting-edge developments always take the existing system components into account; another great advantage, meaning that your exisiting stock remains compatible and easily integrated into the latest designs. It goes without saying that all of the tent components are available for years to come.

Creativity is limitless with the uniflex system. A host of accessories, such as glass or hard-PVC system elements (at side height of 3.40 and 4.00 m), system cassette flooring, aluminum doors, ramps, decoration and more, are available to transform the Losberger De Boer uniflex system into stylish, individual space solutions for any application.



Dimensions

Туре	Profile	Frame ID#	Truss Profile	Width	Leg	Truss-	Rafter Selections	
						distance	Standard	Optional
uniflex	P3N	3	7 3/4" x 4 3/4" 200 mm x 120 mm	10 m	280/340/400/540 cm	· · ·	5.0 m	-
				12 m	280/340/400 cm		6.0 m	-
				15 m	280/340/400 cm		7.5 m	5.0 m + 2.5 m
				20 m	280/340/400 cm		10.0 m	7.5 m + 2.5 m
				25 m	280/340/400 cm		7.5 m + 5.0 m	10.0 m + 2.5 m
uniflex	P2N		9 3/4" x 4 3/4" 250 mm x 120 mm	20 m	280/340/400 cm	5 m/16'	10.0 m	-
				25 m	280/340/400 cm		10.0 m + 2.5 m	7.5 m + 5.0 m
				30 m	280/340/400 cm		10.0 m + 5.0 m	7.5 m + 7.5 m

Technology

Modular character for diverse combination and expansion. Trouble-free transport, storage and maintenance. Assembly with and without Losberger De Boer system cassette flooring possible. A host of accessories and special equipment. All system components are standard stock parts for fast availability. The interchangeable tent components within the system enable various configurations, different widths and extensions without expensive special solutions.

Covers

Textile covers made of polyester fabric, coated with PVC on both sides. Curtains with PVC-gliders for easy fitting in curtain groove. Side and gable curtains with standard plug fastening, lace and grommet or zippers. Side curtains with windows available in several attractive designs. System wall elements are available in glass or hard-PVC.









Frame

Trusses of extruded 4-groove aluminum hollow profiles, maintenance-free, all aluminum components technically anodized. Steel parts are hot-dip galvanized. Truss distance 5m. Roof slope 18 degrees. Integrated curtain groove in eave purlins and gable wall beams. Prepared for a subsequent installation of system cassette wall elements of hard-PVC or glass. Structural lengths in 5 m increments. Exact joining of various Losberger De Boer large and small tent systems possible.

Accessories & special equipment

- Roof covers and side curtains of transparent foil
- Aluminum doors (double-wing/one-wing)
- Glass & Cassette wallCassette floors
- Ramps at entrances
- Textile beam gutter or beam flap and many more...

For more details please visit our website www.losbergerdeboer.com

Losberger De Boer 285 Bucheimer Rd Suite A Frederick, MD 21701 Phone: 1-301-682-8000 Fax: 1-301-682-8005 E-Mail: LosbergerUS@losbergerdeboer.com www.losbergerus.com .512/werbemacher